

Saturday's Purse

©2010 Liz Friswell

TLQ 006

Saturday's seem to be my day to be creative.
So this will be the Saturday club patterns.

Fabric Requirements

A Batik for the front of the bag	1m
B Lining fabric	.5m
Magnetic closures	2
SF101™ Pellon woven fusible	2m
17- 18 inch zipper	1
Belt for handle	1
Thread to match outer fabric	
Pkg D rings	1
Scissor pal for the zipper pull	1

Tiger Lily Quilts

1228 4th Street

Estevan, Sk. 306-634-2900

www.tigerlilyquilts.com

Saturday's Purse

© By Liz Friswell



Tiger Lily Quilts

www.tigerlilyquilts.com

Saturday's Purse

bottom, repeat for the other three corners. Cut off excess but check that it is right before you do.*Make sure that you line up side seam with the bottom seam.

- Turn Right side out. Press
- Make the tabs wide enough for your belt/D ring. Sew 2 tubes turn right sides out and topstitch. Loop tab around the Belt/D ring first then sew to your Purse. Attach Tabs the first seam of the square box is 1 inch above outer pocket, make sure that you have centered the tab across the side seams.
- Attach Scissor pals to your tab of the zipper.
- If you don't have a belt use a Scarf or Make a strap by sewing a tube that is cut to the length and width that you want. You could add batting/cording to add padding.

Enjoy!!!!©

Thanks for buying one of My Patterns
Any questions or corrections email me at
tigerlilyquilts@sasktel.net

Cutting Instructions: wof is the width of fabric
Fabrics A, B

Cut 3 rectangles 16 x 18 for front, back and front pocket of purse

Cut 5 rectangles 16 x 18 from the SF101™

Cut 2 rectangles 16 x 18 from the lining fabric

Cut 2 rectangles 10 x 10 for the pocket inside and out.

Cut 2 rectangles for the tabs the size depends on the belt and D rings that you use make sure that you add the seam allowances.

Sewing instructions: Seams are all $\frac{1}{2}$ inch unless otherwise stated


Iron the SF101™ to wrong side of each panel for the purse, front, back, and pocket. Do the same for the lining panels. This gives the purse strength for all the weight that you will throw in it.

- Sew the zipper to the main fabric on the 16" side. Line up the zipper edge with the fabric edge right sides together sew with a zipper foot $\frac{1}{4}$ inch away from the teeth. Do the same for the other side making sure you line up the zipper. (I like you to do this first so we know which way is up.)
- Fold the pocket in half right sides together sew on three sides leaving an opening to turn right side out to give you a 4 x 9 Pocket. Center and attach to one

side of lining sewing around three sides and then sew two lines down to give you more pockets. Any size you want (comb, cell phone, passport). Repeat for the front inner pocket placing pocket bottom 2.5' from bottom. * making sure that your pocket opening is facing up the right way. Ask how we know? ☺

- Fold the last main fabric piece in half for the pocket. From the folded edge topstitch $\frac{1}{4}$ " down and $\frac{1}{4}$ " from the first row of stitching.


- Attach the magnetic Closures $1\frac{1}{2}$ " down from the zipper following manufactures directions I did put in extra sf101 in that area.



1. Place a magnetic closure $7\frac{1}{2}$ " from the top of the zipper on the main bag it will be under the front pocket. Attach the other part of the magnetic closure on the inside of the Pocket make sure that your bottom of the pocket lines up with the bottom of your front. Don't go through the front of the pocket.
2. Another magnetic closure needs to be put on the front of the Pocket this is the other half of the one that you put near the top of the front of the Purse. Lower the top so see

exactly where the placement should be, around $7\frac{1}{2}$ " from the bottom of the purse.

- Pin pocket to the bottom edge of the front of the purse; baste down the sides and the bottom.
- Sandwich the zipper between the main fabric and the lining and sew with your zipper foot over your previous seam. Iron and topstitch $\frac{1}{8}$ " from the edge down from the zipper teeth securing the lining and main fabric.
- Lay right sides together; lining and Front fabrics. Starting at the bottom of the lining sew around and remember to leave an opening at the bottom of the lining to so you can turn it right side out. * leave the zipper open about 3 inches. Yes you can sew over the zipper keeping it lined up.



- Now we make the boxed bottom on both the front and the lining.

